

Model	Maximum bending force (kN)	Bending length(mm)	Side rack spacing (mm)	Throat depth (mm)	Maximum cylinder stroke (mm)	The distance between the table and the upper beam (mm)	Main power (kW)	Speed(mm/s)			Dimensions(mm)			Weight(kg)
								Approaching speed	Working speed	Returning speed	Length	Width	Height	
BDE5016	500	1600	1200	250	160	460	4	180	0-10	160	2160	1245	2205	3000
BDE6325	630	2500	2100	350	160	460	5.5	180	0-10	160	3040	1385	2450	4300
BDE8025	800	2500	2100	350	160	465	7.5	180	0-10	160	3040	1385	2450	5000
BDE8032	800	3200	2600	350	160	465	7.5	180	0-10	160	3740	1385	2450	6000
BDE10025	1000	2500	2100	400	200	480	7.5	180	0-10	160	3060	1595	2600	6300
BDE10032	1000	3200	2600	400	200	480	7.5	180	0-10	160	3700	1595	2650	6600
BDE10042	1000	4200	3600	400	200	480	7.5	180	0-10	160	4700	1595	2650	8300
BDE13032	1300	3200	2600	400	200	480	11	180	0-10	160	3720	1575	2650	6800
BDE13042	1300	4200	3600	400	200	480	11	180	0-10	160	4720	1575	2650	8500
BDE17032	1700	3200	2600	400	200	480	11	180	0-10	160	3720	1650	2730	8400
BDE17042	1700	4200	3600	400	200	480	11	180	0-10	160	4720	1650	2730	9800
BDE17050	1700	5000	4000	400	200	480	11	180	0-10	160	5600	1800	2960	13800
BDE17060	1700	6000	5000	400	200	480	15	180	0-10	160	6630	1800	3160	16500
BDE20032	2000	3200	2600	400	200	480	15	180	0-10	160	3740	1695	2870	9650
BDE20042	2000	4200	3400	400	200	480	15	180	0-10	160	4640	1695	2870	11500
BDE20050	2000	5000	4000	400	200	480	15	180	0-10	160	5630	1850	3100	15000
BDE20060	2000	6000	5000	400	200	480	18.5	180	0-10	160	6630	1850	3210	17500
BDE25032	2500	3200	2600	400	250	500	18.5	160	0-8	120	3760	1700	3015	12000
BDE25042	2500	4200	3400	400	250	500	18.5	160	0-8	120	4660	1700	3015	14800
BDE25050	2500	5000	4000	400	250	500	18.5	160	0-8	120	5650	1920	3125	17800
BDE25060	2500	6000	5000	400	250	500	22	160	0-8	120	6650	1920	3325	20500
BDE32032	3200	3200	2600	500	250	500	22	160	0-8	120	3780	1800	3375	14600
BDE32042	3200	4200	3400	500	250	500	22	160	0-8	120	4680	1800	3375	18000
BDE32050	3200	5000	4000	500	250	500	22	140	0-8	110	5830	2150	3690	23500
BDE32060	3200	6000	5000	500	250	500	22	140	0-8	110	6830	2150	3855	27800
BDE40032	4000	3200	2600	500	300	600	30	110	0-8	110	3460	2350	3600	25700
BDE40042	4000	4200	3400	500	300	600	30	110	0-8	110	4260	2350	3600	28500
BDE40050	4000	5000	4000	500	300	600	30	100	0-8	100	5260	2350	4700	34700
BDE40060	4000	6000	5000	500	300	600	30	100	0-8	100	6260	2350	5000	40000
BDE50032	5000	3200	2600	500	300	600	37	90	0-7	90	3480	2580	4600	33000
BDE50042	5000	4200	3400	500	300	600	37	90	0-7	90	4260	2580	4700	37000
BDE50050	5000	5000	4000	500	300	600	37	90	0-7	90	5260	2580	4900	42000
BDE50060	5000	6000	5000	500	300	600	37	90	0-7	90	6260	2580	5200	47000
BDE60042	6000	4200	3400	550	300	600	45	90	0-7	90	4260	3530	4950	46000
BDE60050	6000	5000	4000	550	300	600	45	90	0-7	90	5260	3530	5050	52000
BDE60060	6000	6000	5000	550	300	600	45	90	0-7	90	6260	3530	5200	59000

